


## Poured concrete spacer round



The poured concrete spacer has a round contact surface. The double clamp clamps well to the reinforcing steel. The spacer can be installed on both vertical and horizontal reinforcement. Installation is possible on reinforcement Ø 6-16 mm.

Article description	Title of variant	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Packaging piece/pallet	Weight kg/100 pieces
23143000	Cast concrete spacer GB Round 25 K2 (double clamp)	25	480 pieces/bag	14400	4,600
23144000	Cast concrete spacer GB Round 30 K2 (double clamp)	30	400 pieces/bag	12000	6,080
23145000	Cast concrete support GB Round 35 K2 (double clamp)	35	320 pieces/bag	9600	7,850
23146000	Cast concrete support GB Round 40 K2 (double clamp)	40	240 pieces/bag	7200	9,690
23147000	Cast concrete support GB Round 45 K2 (double clamp)	45	240 pieces/bag	7200	11,280
23148000	Cast concrete spacer GB Round 50 K2 (double clamp)	50	160 pieces/bag	4800	13,130
23150000	Cast concrete support GB Round 60 K2 (double clamp)	60	160 pieces/bag	3840	18,180