


## Poured concrete spacer with eyelet wire



The GB ÖD cast concrete shoring with eyelet wire can be used with horizontal and vertical reinforcement. The large contact area makes the GB ÖD very stable and highly resilient. The Bipo is manufactured with a round, flat contact surface. The inserted eyelet wire is galvanized.

Article description	Title of variant	Concrete cover mm	a mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Packaging piece/pallet	Weight kg/100 pieces
23170000	GB 20 ÖD cast concrete support with eyelet wire	20	40	240 pieces/bag	8640	5,800
23171000	GB 25 ÖD poured concrete support with eyelet wire	25	40	240 pieces/bag	8640	7,200
23172000	GB 30 ÖD poured concrete support with eyelet wire	30	40	240 pieces/bag	8640	8,870
23173000	GB 35 ÖD poured concrete support with eyelet wire	35	40	160 pieces/bag	5760	10,300
23174000	GB 40 ÖD cast concrete support with eyelet wire	40	40	160 pieces/bag	5760	12
23175000	GB 45 ÖD poured concrete support with eyelet wire	45	40	160 pieces/bag	5760	13,560
23176000	GB 50 ÖD poured concrete support with eyelet wire	50	40	160 pieces/bag	4800	15,590
23177000	GB 60 ÖD cast concrete support with eyelet wire	60	40	128 pieces/bag	3840	18,620