


## Kapo with studs



The Kapo is mainly mounted on standing reinforcement. Installation is possible on reinforcement  $\varnothing$  3-10 mm. To prevent twisting, the Kapo is mounted on a reinforcement crossing point. The spring steel clamp  $\varnothing$  2 mm clamps the Kapo optimally to the reinforcing steel. Quick installation is guaranteed. The studded contact surface produces a very good exposed concrete surface. The concrete can also be supplied in other colors on request.

## Kapo with studs

Article description	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22118300	Kapo 25/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	25	500 pieces/bag	3,600	10.000
22119300	Kapo 30/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	30	500 pieces/bag	4,200	10.000
22120300	Kapo 35/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	30	35	500 pieces/bag	5,100	10.000
22121300	Kapo 40/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	35	40	250 pieces/bag	6,800	5.000
22122300	Kapo 45/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	35	45	250 pieces/bag	8,100	5.000
22123300	Kapo 50/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	50	200 pieces/bag	10,500	4.000
22124300	Kapo 55/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	55	175 pieces/bag	12,200	3.500
22125300	Kapo 60/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	40	60	150 pieces/bag	14,400	3.000
22126300	Kapo 65/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	50	65	125 pieces/bag	17	2.500
22127300	Kapo 70/3-10 N with studs (trough for reinforcing steel Ø 3-10 mm)	50	70	100 pieces/bag	19,700	2.000