


## Kapo clamps



The Kapo is mainly mounted on standing reinforcement. Installation is possible on reinforcement  $\varnothing$  3-10 mm. To prevent twisting, the Kapo is mounted on a reinforcement crossing point. The two spring steel clamps  $\varnothing$  2 mm clamp the Kapo optimally to the reinforcing steel. Quick installation is guaranteed. Due to the small contact surface, a very good exposed concrete surface is achieved. The concrete can also be supplied in other colors on request.

## Kapo clamps

Article description	Title of variant	Length mm	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22118400	Kapo 25/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	25	500 pieces/bag	3,600	10.000
22119400	Kapo 30/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	30	500 pieces/bag	4,200	10.000
22120400	Kapo 35/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	30	35	500 pieces/bag	5,100	10.000
22121400	Kapo 40/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	35	40	250 pieces/bag	6,800	5.000
22122400	Kapo 45/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	35	45	250 pieces/bag	8,100	5.000
22123400	Kapo 50/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	50	200 pieces/bag	10,500	4.000
22124400	Kapo 55/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	55	175 pieces/bag	12,200	3.500
22125400	Kapo 60/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	40	60	150 pieces/bag	14,400	3.000
22126400	Kapo 65/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	50	65	125 pieces/bag	17	2.500
22127400	Kapo 70/3-10 K2 2 clamps (trough for reinforcing steel Ø 3-10 mm)	50	70	100 pieces/bag	19,700	2.000