

Elevation BWA acid-resistant

The BWA is mounted at the end of the reinforcement. Installation is possible on reinforcement Ø 3-10 mm. The plastic clip ensures a secure hold. The insertion depth is 20 mm. The concrete is chemically resistant.

Article description	Title of variant	Concrete cover mm	H mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22610600	Elevation BWA 20 (FB round Ø35 mm) acid-resistant	20	40	500 pieces/bag	7	12.000
22611600	Elevation BWA 25 (FB round Ø35 mm) acid-resistant	25	45	500 pieces/bag	7,900	12.000
22612600	Elevation BWA 30 (FB round Ø35 mm) acid-resistant	30	50	500 pieces/bag	8,800	10.000
22613600	Elevation BWA 35 (FB round Ø35 mm) acid-resistant	35	55	400 pieces/bag	9,600	8.000
22614600	Elevation BWA 40 (FB round Ø35 mm) acid-resistant	40	60	400 pieces/bag	10,500	8.000
22615600	Elevation BWA 45 (FB round Ø35 mm) acid-resistant	45	65	250 pieces/bag	11,400	6.000
22616600	Elevation BWA 50 (FB round Ø35 mm) acid-resistant	50	70	250 pieces/bag	12,300	6.000
22617600	BWA special sizes acid-resistant					