


## Roka-L acid-resistant



The Roka-L with longitudinal groove is mounted on the vertical reinforcing steel. The two spring steel clamps Ø 2 mm are placed over the horizontal reinforcing steel and clamp the Roka optimally to the reinforcing steel. Quick installation is guaranteed. The bevel is used to guide the reinforcement cage into the formwork. This prevents the formwork from catching on the spacer. The point-shaped contact surface produces a very good exposed concrete surface. The groove width and depth are produced as required.



Article description	Title of variant	Concrete cover mm	Weight kg/100 pieces	Packaging piece/gibo
22242300	Roka-L with longitudinal groove 25 acid-resistant	25	5	8.000
22243300	Roka-L with longitudinal groove 30 acid-resistant	30	6,100	7.000
22244300	Roka-L with longitudinal groove 35 acid-resistant	35	8	6.000
22245300	Roka-L with longitudinal groove 40 acid-resistant	40	10,100	5.000
222452100	Roka-L with longitudinal groove 45 acid-resistant	45	12,100	4.500
22247900	Roka-L with longitudinal groove 50 acid-resistant	50	14,900	4.000
22248300	Roka-L with longitudinal groove 60 acid-resistant	60	21,100	3.500
22249300	Roka-L with longitudinal groove 70 acid-resistant	70	28,100	3.000