

Bipo oD without wire

The Bipo without wire is used with horizontal reinforcement. The Bipo is manufactured with a flat contact surface as standard and can also be supplied with a trough on request. The Bipo contains a hole through which the user can insert a binding wire.

Article description	Title of variant	Concrete cover mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Packaging piece/pallet	Weight kg/100 pieces
22166000	Bipo 25 oD without wire	25	20	750 pieces/bag	24000	3,200
22167000	Bipo 30 oD without wire	30	22	500 pieces/bag	16000	3,700
22168000	Bipo 35 oD without wire	35	22	500 pieces/bag	16000	4,200
22169000	Bipo 40 oD without wire	40	22	500 pieces/bag	16000	5,800
22170000	Bipo 45 oD without wire	45	22	250 pieces/bag	8000	7,100
22171000	Bipo 50 oD without wire	50	22	250 pieces/bag	8000	7,800
22172000	Bipo 55 oD without wire	55	22	250 pieces/bag	8000	8,700
22173000	Bipo 60 oD without wire	60	24	200 pieces/bag	6400	9,800
22174000	Bipo 65 oD without wire	65	24	200 pieces/bag	6400	10,300
22174100	Bipo 70 oD without wire	70	24	175 pieces/bag	5600	11
22174200	Bipo 75 oD without wire	75	24	175 pieces/bag	5600	11,800
22174300	Bipo 80 oD without wire	80	24	150 pieces/bag	4800	12,200