


## Dreika K2 N two clamps and studs



The Dreika K2 N is used with upright reinforcement. N stands for the dimpled contact surface. The dimpled surface means that the spacer is not in full contact with the formwork and is only slightly visible on the concrete surface after concreting. The length of the Dreika is designed for a rebar spacing of up to max. 15 cm. Two steel clamps Ø1.5 mm are fitted at the factory. The Dreika can be mounted on reinforcing steel Ø 6-14 mm. The clamps ensure very quick installation. Thanks to its fastening and elongated shape, the Dreika is tilt-proof and stable.

## Dreika K2 N two clamps and studs

Article description	Title of variant	Concrete cover mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22210900	Dreika 20/18 K2 N with two clamps for Ø6-14 mm and studs	20	180	180 pieces/bag	11	8.000
22211900	Dreika 25/18 K2 N with two clamps for Ø6-14 mm and studs	25	180	175 pieces/bag	13	7.500
22212900	Dreika 30/18 K2 N with two clamps for Ø6-14 mm and studs	30	180	150 pieces/bag	18	5.000
22213900	Dreika 35/18 K2 N with two clamps for Ø6-14 mm and studs	35	180	125 pieces/bag	23	4.000
22214900	Dreika 40/18 K2 N with two clamps for Ø6-14 mm and studs	40	180	100 pieces/bag	24	3.500
22215900	Dreika 45/18 K2 N with two clamps for Ø6-14 mm and studs	45	180	75 pieces/bag	27	2.500
22216900	Dreika 50/18 K2 N with two clamps for Ø6-14 mm and studs	50	180	70 pieces/bag	30	2.000
22217900	Dreika 55/18 K2 N with two clamps for Ø6-14 mm and studs	55	180	65 pieces/bag	33	1.500
22218900	Dreika 60/18 K2 N with two clamps for Ø6-14 mm and studs	60	180	60 pieces/bag	37	1.250
22219900	Dreika 70/18 K2 N with two clamps for Ø6-14 mm and studs	70	180	55 pieces/bag	40	1.100
22231900	Dreika 80/18 K2 N with two clamps for Ø6-14 mm and studs	80	180	50 pieces/bag	44	1.000