


Dreika K2 N with knobs and two clamps



The Dreika K2 N is used with upright reinforcement. N stands for the dimpled contact surface. The dimpled surface means that the spacer is not in full contact with the formwork and is only slightly visible on the concrete surface after concreting. The length of the Dreika is designed for a rebar spacing of up to max. 27 cm. Two steel clamps Ø1.5 mm are fitted at the factory. The Dreika can be mounted on reinforcing steel Ø 6-14 mm. The clamps ensure very quick installation. Thanks to its fastening and elongated shape, the Dreika is tilt-proof and stable.



Dreika K2 N with knobs and two clamps

Article description	Title of variant	Concrete cover mm	L mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/100 pieces	Packaging piece/gibo
22220900	Dreika 20/30 K2 N with knobs and two clamps for Ø6-14 mm	20	300	150 pieces/bag	19	8.000
22221900	Dreika 25/30 K2 N with knobs and two clamps for Ø6-14 mm	25	300	150 pieces/bag	21,700	7.500
22222900	Dreika 30/30 K2 N with studs and two clamps for Ø6-14 mm	30	300	100 pieces/bag	30	5.000
22223900	Dreika 35/30 K2 N with knobs and two clamps for Ø6-14 mm	35	300	100 pieces/bag	38,300	4.000
22224900	Dreika 40/30 K2 N with knobs and two clamps for Ø6-14 mm	40	300	75 pieces/bag	40	3.500
22225900	Dreika 45/30 K2 N with knobs and two clamps for Ø6-14 mm	45	300	60 pieces/bag	45	2.500
22226900	Dreika 50/30 K2 N with knobs and two clamps for Ø6-14 mm	50	300	60 pieces/bag	50	2.000
22227900	Dreika 55/30 K2 N with knobs and two clamps for Ø6-14 mm	55	300	55 pieces/bag	55	1.500
22228900	Dreika 60/30 K2 N with studs and two clamps for Ø6-14 mm	60	300	50 pieces/bag	61,700	1.250
22229900	Dreika 70/30 K2 N with studs and two clamps for Ø6-14 mm	70	300	45 pieces/bag	66,700	1.100
22241900	Dreika 80/30 K2 N with knobs and two clamps for Ø6-14 mm	80	300	40 pieces/bag	73,300	1.000