


## Boomerang L=33 without pimples



The boomerang is a surface spacer and is used with horizontal reinforcement. The contact surface is not studded and should therefore be used in subordinate components without high exposed concrete requirements. The 33 cm length is suitable for use with R reinforcing steel mesh with a mesh size of 15x25 cm. Due to the bend, the boomerang is stable in position and does not tip over.

Article description	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22283200	Boomerang 20/33, L = 33 cm without pimples	20	17	330	4000	17,200
22283300	Boomerang 25/33, L = 33 cm without pimples	25	17	330	3800	18,100
22284100	Boomerang 30/33, L = 33 cm without pimples	30	19	330	3500	19,800
22285100	Boomerang 35/33, L = 33 cm without pimples	35	19	330	3200	31,700
22286100	Boomerang 40/33, L = 33 cm without pimples	40	25	330	1750	33
22287100	Boomerang 45/33, L = 33 cm without pimples	45	25	330	1500	36
22288100	Boomerang 50/33, L = 33 cm without pimples	50	25	330	1500	39,600
22289100	Boomerang 55/33, L = 33 cm without knobs	55	25	330	1250	56,800
22290100	Boomerang 60/33, L = 33 cm without pimples	60	25	330	1100	66