


Boomerang L=33 mit Noppen



The boomerang is a surface spacer and is used with horizontal reinforcement. The contact surface is studded and is very suitable for components with exposed concrete requirements. The 33 cm length is used with Q reinforcing steel meshes with a mesh size of 25x15 cm. Due to the bend, the boomerang is stable in position and does not tip over.

Article description	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22283100	Boomerang 20/33 N, L = 33 cm with pimples	20	17	330	4000	17,200
22283000	Boomerang 25/33 N, L = 33 cm with pimples	25	17	330	3800	18,100
22284000	30/33 N boomerang, L = 33 cm mit Noppen	30	19	330	3500	19,800
22285000	Boomerang 35/33 N, L = 33 cm with pimples	35	19	330	3200	31,700
22286000	40/33 N boomerang, L = 33 cm mit Noppen	40	25	330	1750	33
22287000	Boomerang 45/33 N, L = 33 cm with pimples	45	25	330	1500	36
22288000	Boomerang 50/33 N, L = 33 cm with pimples	50	25	330	1500	39,600
22289000	Boomerang 55/33 N, L = 33 cm with pimples	55	25	330	1250	56,800
22290000	Boomerang 60/33 N, L = 33 cm with pimples	60	25	330	1100	66