


## Eel N L=50 with knobs



The Aal 20/50 N is a surface spacer and is used, for example, in the area of ceilings and beams with horizontal reinforcement. The contact surface is dimpled. The concrete runs under the studs. Ideal for exposed concrete surfaces. The two bends make it tilt and position-proof. Quick installation is guaranteed.

Article description	Title of variant	Concrete cover mm	a mm	L mm	Packaging piece/pallet	Weight kg/100 pieces
22363000	Aal 20/50 N, L = 50 cm mit Noppen	20	17	500	3300	28
22366000	eel 25/50 N, L = 50 cm with knobs	25	17	500	3000	29,700
22367000	Eel 30/50 N, L = 50 cm with knobs	30	19	500	2750	30,600
22368000	Aal 35/50 N, L = 50 cm with knobs	35	19	500	2650	32,500
22369000	Aal 40/50 N, L = 50 cm mit Noppen	40	25	500	1460	49
22370000	Aal 45/50 N, L = 50 cm with knobs	45	25	500	1450	54,600
22371000	Eel 50/50 N, L = 50 cm with knobs	50	25	500	1250	60,400
22372000	Aal 55/50 N, L = 50 cm with studs	55	25	500	1100	76,800
22373000	Eel 60/50 N, L = 50 cm with knobs	60	25	500	850	94,400