


## Round profile



The round profile is a surface spacer and is used in precast plants and in the area of floor slabs with horizontal reinforcement. The round contact surface is suitable for transferring loads over a large area into the substrate. The round profile is stable and has a good load-bearing capacity. It is suitable for use with medium-weight reinforcement and where high traffic loads occur. Quick installation is guaranteed. It is also possible to produce the round profiles in short pieces in accordance with the DBV spacer leaflet (L<350 mm).

Article description	Title of variant	Concrete cover mm	L mm	Packaging metre/pallet	Weight kg/metre
22619000	Round 20, L = 120 cm	20	1.200	1.299,600	0,800
22620000	Round 25, L = 120 cm	25	1.200	1.000,800	1,100
22622000	Round 30, L = 120 cm	30	1.200	702	1,600
22624000	Round 35, L = 120 cm	35	1.200	702	2,100
22625000	Round 40, L = 120 cm	40	1.200	432	2,600
22626000	Round 50, L = 120 cm	50	1.200	270	3,900
22627000	Round 60, L = 120 cm	60	1.200	200,400	5,700
22628000	Round 70, L = 120 cm	70	1.200	180	7,900
22629000	Round 80, L = 120 cm	80	1.200	99,600	10,100
22630000	Round 90, L = 120 cm	90	1.200	80,400	13
22631000	Round 100, L = 120 cm	100	1.200	60	15,700