Universal lining tube 150



Enables sealing in all types of wall thanks to the combination of the preparation flange and 3-web gaskets

Applications, features, properties and benefits
Low weight, easy installation in the formwork, can be cut to length on site, can be used in all wall types including element construction methods, tested solution for use in fresh concrete composite systems,
Preparation flange for practical preparation of plastic-modified thick bitumen coatings, resistant to breakage, dimensionally stable, sealed ready for installation, gas- and watertight. DIN 18533 W1-E, DIN 18533 W2.1-E, waterproof concrete stress class 1, waterproof concrete stress class 2

Scope of delivery
2 sealing caps

Application
all wall types

Assembly
After placement in the formwork, the UFR is set in concrete. Plastic-modified bitumen thick coatings or fresh concrete composite systems can then be applied to the preparation flange

Article description	Title of variant	Length mm	Lining pipe Øi mm (D1)	Lining pipe Øa mm (D2)	Machining flange Øa Surface dimension mm (D3)	Processing flange Øa edge dimension mm (D4)	Tube length mm (L)	Weight kg/piece
78300251	UFR150/200	200	150	162	282	260	200	1,160
78300252	UFR150/240	240	150	162	282	260	240	1,320
78300253	UFR150/25	250	150	162	282	260	250	1,340
78300254	UFR150/300	300	150	162	282	260	300	1,540
78300255	UFR150/365	365	150	162	282	260	365	1,780
78300256	UFR150/400	400	150	162	282	260	400	1,900
78300257	UFR150/500	500	150	162	282	260	500	2,280