Universal feed tube 100



Enables sealing in all types of wall thanks to the combination of the preparation flange and 3-web gaskets

Applications, features, properties and benefits
Low weight, easy installation in the formwork, can be cut to length on site, can be used in all wall types including element construction methods, tested solution for use in fresh concrete composite systems,
Preparation flange for practical preparation of plastic-modified thick bitumen coatings, resistant to breakage, dimensionally stable, sealed ready for installation, gas- and watertight. DIN 18533 W1-E, DIN 18533 W2.1-E, waterproof concrete stress class 1, waterproof concrete stress class 2

Scope of delivery
2 sealing caps

Application
all wall types

Assembly
After placement in the formwork, the UFR is set in concrete. Plastic-modified bitumen thick coatings or fresh concrete composite systems can then be applied to the preparation flange

Article description	Title of variant	Length mm	Lining pipe Øi mm (D1)	Lining pipe Øa mm (D2)	Machining flange Øa Surface dimension mm (D3)	Processing flange Øa edge dimension mm (D4)	Tube length mm (L)	Weight kg/piece
78300244	UFR100/200	200	100	110	227	210	200	0,660
78300245	UFR100/240	240	100	110	227	210	240	0,780
78300246	UFR100/250	250	100	110	227	210	250	0,800
78300247	UFR100/300	300	100	110	227	210	300	0,900
78300248	UFR100/365	365	100	110	227	210	365	1,040
78300249	UFR100/400	400	100	110	227	210	400	1,100
78300250	UFR100/500	500	100	110	227	210	500	1,530