Universal feed tube 200



Enables sealing in all types of wall thanks to the combination of the preparation flange and 3-web gaskets

Applications, features, properties and benefits
Low weight, easy installation in the formwork, can be cut to length on site, can be used in all wall types including element construction methods, tested solution for use in fresh concrete composite systems,
Preparation flange for practical preparation of plastic-modified thick bitumen coatings, resistant to breakage, dimensionally stable, sealed ready for installation, gas- and watertight. DIN 18533 W1-E, DIN 18533 W2.1-E, waterproof concrete stress class 1, waterproof concrete stress class 2

Scope of delivery
2 sealing caps

Application
all wall types

Assembly
After placement in the formwork, the UFR is set in concrete. Plastic-modified bitumen thick coatings or fresh concrete composite systems can then be applied to the preparation flange

Article description	Title of variant	Length mm	Lining pipe Øi mm (D1)	Lining pipe Øa mm (D2)	Machining flange Øa Surface dimension mm (D3)	Processing flange Øa edge dimension mm (D4)	Tube length mm (L)	Weight kg/piece
78300258	UFR200/200	200	200	214	336	311	200	1,740
78300259	UFR200/240	240	200	214	336	311	240	1,960
78300260	UFR200/250	250	200	214	336	311	250	2,020
78300261	UFR200/300	300	200	214	336	311	300	2,160
78300262	UFR200/365	365	200	214	336	311	365	2,700
78300263	UFR200/400	400	200	214	336	311	400	2,920
78300264	UFR200/500	500	200	214	336	311	500	3,480