

## Universal wall bushing 100/KG2000

Flow-optimized wall feed-through - prevents deposits and backflow in the wastewater system. Enables sealing in double/element walls thanks to three 3-web seals

### Applications, features, properties and benefits

Available ready-to-install to wall thickness, three 3-web seals for use in double/element walls, pressure-tight after concreting, for installation flush with formwork, blind-sealed ready-to-install, available in KG and KG2000 quality, no change in flow direction, with integrated preparation flange. gas-tight and watertight. DIN 18533 W1-E, DIN 18533 W2.1-E, waterproof concrete stress class 1, waterproof concrete stress class 2

### Scope of delivery

1 piece rubber sleeve with integrated 3-web seal, 1 piece clamping band, 1 piece sleeve cover with preparation flange and blind cover for hammering in, 2 additional 3-web seals, 1 piece lamella plug, 1 piece KG (2000) pipe (pre-assembled ready for installation)

### Application

all wall types

### Assembly

After placement in the formwork, the UDME is set in concrete. Plastic-modified bitumen thick coatings can then be applied to the preparation flange

| Article description | Title of variant   | Length mm | Media pipe Øa mm | Weight kg/piece |
|---------------------|--------------------|-----------|------------------|-----------------|
| 78300222            | UDME100/240 KG2000 | 240       | 110              | 1,300           |
| 78300224            | UDME100/250 KG2000 | 250       | 110              | 1,300           |
| 78300227            | UDME100/300 KG2000 | 300       | 110              | 1,350           |
| 78300229            | UDME100/365 KG2000 | 365       | 110              | 1,450           |
| 78300231            | UDME100/400 KG2000 | 400       | 110              | 1,590           |