




BETOMAX® 15



Weldable and bendable tie rod fully threaded. Compatible with all accessories of the Uni 15 system.

On request these tie rods can be supplied in special cut lengths, even in galvanized version.

Tie rods in stainless steel (grade 1.4404/TP 3161), article 18554404, are also available ex stock.

Usable length for item no. 18553200 approx. 3.15 meter.

Usable length for item no. 18559999 approx. 6.30 meter.

Technische Daten

External diameter a	17 mm
Core diameter b	15 mm
Gradient c	10 mm
Working load	Value according to approval kN
Yield strength - values according to approval	142 kN
Partial safety factor for anchor rod - values according to approval	1,150
Partial safety factor for the load - values according to approval	1,500

BETOMAX® 15

Article description	Length	Length cm	Comment/footnote on the variant	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/piece
18550200		20		1 piece	0,310
18550250		25		1 piece	0,390
18550300		30		1 piece	0,470
18550350		35		1 piece	0,540
18550400		40		1 piece	0,620
18550500		50		10 pieces/bunch	0,780
18550750		75		10 pieces/bunch	1,160
18550850		85		10 pieces/bunch	1,320
18551000		100		10 pieces/bunch	1,550
18551250		125		10 pieces/bunch	1,940
18551500		150		10 pieces/bunch	2,330
18551750		175		10 pieces/bunch	2,710
18552000		200		10 pieces/bunch	3,100
18552250		225		1 piece	3,490
18552500		250		1 piece	3,890
18553200		*320	*Usable length: approx. 3.15 m	1 piece	4,960
18559999		**640	**Usable length: approx. 6.30 m	1 piece	9,920
18558899	div. Abmessungen			Meter	1,55
18558989	+ fixed surcharge EUR 0.64/piece				