


## Water stop B 15 round



Compatible with Uni 15.

Cut to length pieces of Dist K - 26 rough tubes can be pushed on to both ends of water stop B15 round, and provide a seal tight enough to prevent concrete from entering. This prevents casting the tie rod in the sleeve.

Adapters are available for Dist K-22 and Dist FB-22.

Use of adapters increases the dimension shown as 70mm to 125mm.

Calculation of tube length (L):

$$LK-26 = (WD - 2c - 70) / 2$$

Calculation of tube length (L)

with adapter and K 22 / FB 22:

$$LK-22/FB 22 = (WD - 2c - 125) / 2$$

### Applications, features, properties and benefits

Round water stops 120 in diameter offer protection against the ingress of water

Conical holes can be filled with mortar or a concrete plug after removal of cones

Concrete cover of 35 or 50mm when used with Cone EX

Concrete cover of 50mm when used with MKK B 15

Article description	Title of variant	Plate size Ø mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/piece
20458420	Water barrier B15 round	120	25 pieces/bag	0,712
20458722	Reducing coupling		250 pieces/bag	0,011
20458109	Sleeve Water barrier B15		25 pieces/bag	0,525