


SD water barrier



Swellable SD type water stop to prevent the ingress of water. Fitted using BETOMAX® SD installation pliers.

New type of sealing ring which utilises synthetic elastomers
Swelling commences automatically upon contact with moisture and wetness

Swelling capacity specifically designed for sealing concrete
Universally applicable with fiber-reinforced concrete, steel distance tubes and plastic tubes with diameters ranging from 22 to 40 mm
Simple fitting and reliable handling when using BETOMAX® SD installation pliers

Calculation of tube length Dist FB 22,
Dist K-22 and Dist ST-22 (L): $L = WD - 2c$

Please order tubes cut to length separately.

Article description	Title of variant	Ø internal mm	Ø external mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/metre
61922888	FB round tube 22, blanks	22	40	Metre	1,760
63122130	Dist K-22 rough, blanks	22	26	Metre	0,210
63126190	Dist K-26 rough, blanks	26	30	Metre	0,240
63132190	Dist K-32 rough, blanks	32	36	Metre	0,285
62022150	Dist St-22, blanks	24,800	26	Metre	0,378
61822381	SD-Ring seal for Dist K-22 to Dist K-32			1 piece	0,017
61822382	SD-Ring seal, large for FB round tube 22			1 piece	0,025
61822400	SD-Assembly pliers			1 piece	0,313