



SD water barrier



Swellable SD type water stop to prevent the ingress of water. Fitted using BETOMAX® SD installation pliers.

New type of sealing ring which utilises synthetic elastomers
Swelling commences automatically upon contact with moisture and wetness

Swelling capacity specifically designed for sealing concrete
Universally applicable with fiber-reinforced concrete, steel distance tubes and plastic tubes with diameters ranging from 22 to 40 mm
Simple fitting and reliable handling when using BETOMAX® SD installation pliers

Calculation of tube length Dist FB 22,
Dist K-22 and Dist ST-22 (L): $L = WD - 2c$

Please order tubes cut to length separately.

| Article description | Title of variant | Ø internal mm | Ø external mm | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/metre |
|---------------------|--|---------------|---------------|---|-----------------|
| 61922888 | FB round tube 22, blanks | 22 | 40 | Metre | 1,760 |
| 63122130 | Dist K-22 rough, blanks | 22 | 26 | Metre | 0,210 |
| 63126190 | Dist K-26 rough, blanks | 26 | 30 | Metre | 0,240 |
| 63132190 | Dist K-32 rough, blanks | 32 | 36 | Metre | 0,285 |
| 62022150 | Dist St-22, blanks | 24,800 | 26 | Metre | 0,378 |
| 61822381 | SD-Ring seal for Dist K-22 to Dist K-32 | | | 1 piece | 0,017 |
| 61822382 | SD-Ring seal, large for FB round tube 22 | | | 1 piece | 0,025 |
| 61822400 | SD-Assembly pliers | | | 1 piece | 0,313 |