



Smoothing cone B15 - B20 - B26.5 and smoothing cone installation



The finishing cone for the perfect concrete surface.

Applications, features, properties and benefits

Recessed installation of the lost anchor rod

Cone can be fitted at precisely 45°

Finishes perfectly flush with the surface

Cone can be easily removed with the help of the extraction tool (for B20 und B26.5)

A connecting nut can be easily fitted once the cone has been pulled

Closing mortaring of the recess with BETOMAX® sealing mortar

MKK Cap 45° B15 for a precise 45° positioning with MKK B15

Use without additional coupling nut

Cap removal without special tool (with carpenter hammer only)

Additional compensation washer available

| Article description | Title of variant | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/piece |
|---------------------|----------------------------------------------|---------------------------------------------------------------------------------|--------------------|
| 18402000 | MKK® Betomax 15 | 25 pieces/bag | 0,500 |
| 18409145 | MKK® cover cap 45° B 15 | 20 pieces/bag | 0,040 |
| 18409146 | Sealing washer for MKK® skew compensation | 100 pieces/bag | 0,001 |
| 18581200 | Anchor holder B 15 | 40 pieces/bag | 0,500 |
| 18409140 | Smoothing cone B 15 45° | 1 piece | 0,075 |
| 14409245 | Smoothing cone B 20 45° | 40 pieces/bag | 0,090 |
| 14581200 | Anchor holder B 20 45° | 40 pieces/bag | 0,500 |
| 21409245 | Smoothing cone B 26.5 45° | 40 pieces/bag | 0,090 |
| 17581200 | Anchor holder B 26.5 45° | 40 pieces/bag | 0,500 |
| 90414500 | Extraction tool | 1 piece | 0,320 |