

2-component adhesive cartridge



Epoxy resin adhesive. For making waterproof resilient joints with fibrous concrete plugs and fair-faced concrete plugs.

Twin cartridge contains components A and B Components blended by mixing nozzle Test report as recommended by German KTW

Processing

Instructions for use:

The surfaces being joined must be free from dust and grease Minimum working temperature 8°C One kg of adhesive ist sufficient for approx. 40 concrete plugs MKK®B 15 One kg of adhesive is sufficient for approx. 150 fibrous concrete plugs FB 22/50 mm

Title of variant	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Weight kg/piece
2-Component adhesive	Duo cartridge A + B	0,820
2-C Squeeze gun	1 piece	1,220
2-C-Squeeze gun	1 piece	1,220
2-C-squeeze gun	1 piece	1,220
Mixer nozzle	1 piece	0,009
Mixer nozzle	1 piece	0,009
Mixer nozzle	1 piece	0,009
	2-Component adhesive 2-C Squeeze gun 2-C-Squeeze gun 2-C-squeeze gun Mixer nozzle Mixer nozzle	metre/ bucket/ bag/ bundle/ box/ can 2-Component adhesive Duo cartridge A + B 2-C Squeeze gun 1 piece 2-C-Squeeze gun 1 piece 2-C-squeeze gun 1 piece Mixer nozzle 1 piece 1 piece