


2-component adhesive cartridge



Epoxy resin adhesive. For making waterproof resilient joints with fibrous concrete plugs and fair-faced concrete plugs.

Twin cartridge contains components A and B

Components blended by mixing nozzle

Test report as recommended by German KTW

Processing

Instructions for use:

The surfaces being joined must be free from dust and grease

Minimum working temperature 8°C

One kg of adhesive is sufficient for approx. 40 concrete plugs MKK®B 15

One kg of adhesive is sufficient for approx. 150 fibrous concrete plugs FB 22/50 mm

| Article description | Title of variant | Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can | Weight kg/piece |
|---------------------|----------------------|--|-----------------|
| 61800300 | 2-Component adhesive | Duo cartridge A + B | 0,820 |
| 61800310 | 2-C Squeeze gun | 1 piece | 1,220 |
| 61800310 | 2-C-Squeeze gun | 1 piece | 1,220 |
| 61800310 | 2-C-squeeze gun | 1 piece | 1,220 |
| 19403020 | Mixer nozzle | 1 piece | 0,009 |
| 19403020 | Mixer nozzle | 1 piece | 0,009 |
| 19403020 | Mixer nozzle | 1 piece | 0,009 |