





COMAX® WU

COMAX® WU Typ B
mit Fugenblech



COMAX® WU Typ S1
mit Fugenblech



Comax® WU - The self-sealing reinforcement connection

Especially for the use of reinforcement connections in WU components
Reinforcement connection in combination with the proven shuttering
elements from the COMAX® board system

A coated FB 120 metal waterstop is used as a sealant

Standard length 1.25 m; box height 30 mm

Comax® WU type B with metal water stop

$h = \text{min. } 18 \text{ cm}$, $b = \text{min. } 14 \text{ cm max. } 53 \text{ cm}$

Comax® WU type S1 with metal water stop

$h = \text{min. } 18 \text{ cm}$, $w = \text{min. } 11 \text{ cm max. } 22 \text{ cm}$

Comment to article

Bitte bei der Bestellung diese Maße angeben:

- BST Ø mm
- Bügelabstände e in cm
- h cm
- b cm
- l cm

COMAX® WU

Article description

Title of variant

412999999

Comax® WU Type B

30791634

AF 200 GK k=45
DF sheet welded with Comax
incl. bumper plate, H = min. 18 cm

41148888

Comax® P 140 WU Type S1

41147777

AF Comax® P 140 FB B2

41168888

Comax® P 160 WU Type S1

41167777

AF Comax® P 160 FB B2

41198888

Comax® P 190 WU Type S1

41197777

AF Comax® P 190 FB B2

41228888

Comax® P 220 WU Type S1

41227777

AF Comax® P 220 FB B2

41248888

Comax® P 240 WU Type S1

41247777

AF Comax® P 240 FB B2