


Type H - hook - type H 2-row - double hook

Typ H Haken



Type H - Type H 2-row


Hooks like standard 60s or 80s. Double row as double hook also available with different steel diameters.

Technical data

The values e , h and l are variable depending on the element width, sheet type and BSt \emptyset . The anchoring length applies only to single-row elements with standard perforation.

Subject to technical changes. The dimensions as well as the combination of the maximum values must be agreed in each individual case. Listed are design examples.

Typ H - 2reihig Doppelhaken



Type H - hook - type H 2-row - double hook

Element width mm	Sheet type P	BSt Ø mm	Bracket spacing e in cm	Bracket height h in cm	Anchoring length for element length 83 cm l in cm	Anchoring length for panel length 125 cm l in cm
60	P	8	10	8 - 98	max. 41	max. 41
60	P	8	15	8 - 98	max. 45	max. 67
60	P	8	20	8 - 98	max. 49	max. 69
60	P	10	10	8 - 98	max. 31	max. 31
60	P	10	15	8 - 98	max. 44	max. 46
60	P	10	20	8 - 98	max. 48	max. 58
60	P	12	10	8 - 98	max. 23	max. 23
60	P	12	15	8 - 98	max. 35	max. 35
60	P	12	20	8 - 98	max. 48	max. 51
80	P	8	10	8 - 98	max. 43	max. 64
80	P	8	15	8 - 98	max. 45	max. 67
80	P	8	20	8 - 98	max. 49	max. 70
80	P	10	10	10 - 98	max. 42	max. 45
80	P	10	15	10 - 98	max. 45	max. 65
80	P	10	20	10 - 98	max. 47	max. 68
80	P	12	10	12 - 98	max. 38	max. 38
80	P	12	15	12 - 98	max. 42	max. 58
80	P	12	20	12 - 98	max. 48	max. 67
110	P/Q/L	8	10	8 - 98	max. 44	max. 64
110	P/Q/L	8	15	8 - 98	max. 46	max. 67
110	P/Q/L	8	20	8 - 98	max. 49	max. 70
110	P/Q/L	10	10	10 - 98	max. 43	max. 63
110	P/Q/L	10	15	10 - 98	max. 44	max. 66
110	P/Q/L	10	20	10 - 98	max. 48	max. 69
110	P/Q/L	12	10	12 - 98	max. 43	max. 62
110	P/Q/L	12	15	12 - 98	max. 44	max. 66
110	P/Q/L	12	20	12 - 98	max. 48	max. 69