


Type BK - bracket stirrup closed

Typ BK Konsole Bügel geschlossen



Type BK

Console bracket closed, only available for bracket widths $b = 90, 120, 140, 170$ and 220 mm.

Also available with bending roller $10 ds$.

Depending on e and l , the stirrups lying in the sheet are bent conically. At max. anchorage length the stirrup tip is $6 ds$.

Technical data

The values $e, b, b1, h$ and l are variable depending on element width, sheet type and BSt \emptyset .

We reserve the right to make technical changes. The dimensions and the combination of the maximum values must be agreed in each individual case. Listed are design examples.

Type BK - bracket stirrup closed

Element width mm	BSt Ø mm	Bracket spacing e in cm	Bracket spacing b in cm	Bracket height h in cm	Anchoring length for element length 83 cm l in cm	Anchoring length for panel length 125 cm l in cm
110	8	10	9	8	7 - 18	7 - 18
110	8	15	9	8	7 - 27	7 - 27
110	8	20	9	8	7 - 36	7 - 36
110	10	10	9	10	9 - 12	9 - 12
110	10	15	9	10	9 - 18	9 - 18
110	10	20	9	10	9 - 24	9 - 24
110	12	15	9	12	11 - 12	11 - 12
110	12	20	9	12	11 - 17	11 - 17
140	8	10	12	8	7 - 32	7 - 32
140	8	15	12	8	7 - 41,5	7 - 48
140	8	20	12	8	7 - 41,5	7 - 62,5
140	10	10	12	10	9 - 24	9 - 24
140	10	15	12	10	9 - 35	9 - 35
140	10	20	12	10	9 - 41,5	9 - 47
140	12	10	12	12	11 - 14	11 - 14
140	12	15	12	12	11 - 21	11 - 21
140	12	20	12	12	11 - 28	11 - 28
160	8	10	14	8	7 - 41	7 - 41
160	8	15	14	8	7 - 41,5	7 - 61
160	8	20	14	8	7 - 41,5	7 - 62,5
160	10	10	14	10	9 - 31	9 - 31
160	10	15	14	10	9 - 41,5	9 - 47
160	10	20	14	10	9 - 41,5	9 - 62
160	12	10	14	12	11 - 21	11 - 21
160	12	15	14	12	11 - 31	11 - 31
160	12	20	14	12	11 - 41	11 - 41
190	8	10	17	8	7 - 41,5	7 - 54
190	8	15	17	8	7 - 41,5	7 - 62,5
190	8	20	17	8	7 - 41,5	7 - 62,5
190	10	10	17	10	9 - 41,5	9 - 43
190	10	15	17	10	9 - 41,5	9 - 62,5
190	10	20	17	10	9 - 41,5	9 - 62,5
190	12	10	17	12	11 - 31	11 - 31
190	12	15	17	12	11 - 41,5	11 - 46
190	12	20	17	12	11 - 41,5	11 - 61
240	8	10	22	8	7 - 41,5	7 - 62,5
240	8	15	22	8	7 - 41,5	7 - 62,5

Type BK - bracket stirrup closed

Element width mm	BSt Ø mm	Bracket spacing e in cm	Bracket spacing b in cm	Bracket height h in cm	Anchoring length for element length 83 cm l in cm	Anchoring length for panel length 125 cm l in cm
240	8	20	22	8	7 - 41,5	7 - 62,5
240	10	10	22	10	9 - 41,5	9 - 62
240	10	15	22	10	9 - 41,5	9 - 62,5
240	10	20	22	10	9 - 41,5	9 - 62,5
240	12	10	22	12	11 - 41,5	11 - 48
240	12	15	22	12	11 - 41,5	11 - 62,5
240	12	20	22	12	11 - 41,5	11 - 62,5