


Type KS - Bracket type for wide cantilever brackets with matching bracket

Typ KS

Konsoltyp für weit auskragende Konsolen mit passendem Steckbügel.



Type KS

Bracket type for wide cantilever brackets with matching plug-in bracket.

The plug-in bracket is supplied and must be bent after bending.

Technical data

The values e , b , h and l are variable depending on element width, sheet type and BSt Ø.

We reserve the right to make technical changes. The dimensions and the combination of the maximum values must be agreed in each individual case. Listed are design examples.

Type KS - Bracket type for wide cantilever brackets with matching bracket

Element width mm	Sheet type P	BSt Ø mm	Bracket spacing e in cm	Bracket spacing b in cm	Bracket height h in cm	Anchoring length for element length 83 cm l in cm	Anchoring length for panel length 125 cm l in cm
80	P	8	10	6	8 - 98	max. 20	max. 20
80	P	8	15	6	8 - 98	max. 31	max. 31
80	P	8	20	6	8 - 98	max. 41,5	max. 42
80	P	10	10	6	10 - 98	max. 14	max. 14
80	P	10	15	6	10 - 98	max. 23	max. 23
80	P	10	20	6	10 - 98	max. 31	max. 31
110	P/Q/L	8	10	8	8 - 98	max. 30	max. 30
110	P/Q/L	8	15	8	8 - 98	max. 41,5	max. 46
110	P/Q/L	8	20	8	8 - 98	max. 41,5	max. 62
110	P/Q/L	10	10	8	10 - 98	max. 23	max. 23
110	P/Q/L	10	15	8	10 - 98	max. 35	max. 35
110	P/Q/L	10	20	8	10 - 98	max. 41,5	max. 48
110	P/Q/L	12	10	8	12 - 98	max. 18	max. 18
110	P/Q/L	12	15	8	12 - 98	max. 28	max. 28
110	P/Q/L	12	20	8	12 - 98	max. 38	max. 38
140	P/Q/L	8	10	11	8 - 98	max. 41,5	max. 45
140	P/Q/L	8	15	11	8 - 98	max. 41,5	max. 62,5
140	P/Q/L	8	20	11	8 - 98	max. 41,5	max. 62,5
140	P/Q/L	10	10	11	10 - 98	max. 35	max. 35
140	P/Q/L	10	15	11	10 - 98	max. 41,5	max. 54
140	P/Q/L	10	20	11	10 - 98	max. 41,5	max. 62,5
140	P/Q/L	12	10	11	12 - 98	max. 28	max. 28
140	P/Q/L	12	15	11	12 - 98	max. 41,5	max. 44
140	P/Q/L	12	20	11	12 - 98	max. 41,5	max. 59
160	P/Q/L	8	10	13	8 - 98	max. 41,5	max. 55
160	P/Q/L	8	15	13	8 - 98	max. 41,5	max. 62,5
160	P/Q/L	8	20	13	8 - 98	max. 41,5	max. 62,5
160	P/Q/L	10	10	13	10 - 98	max. 41,5	max. 44
160	P/Q/L	10	15	13	10 - 98	max. 41,5	max. 62,5
160	P/Q/L	10	20	13	10 - 98	max. 41,5	max. 62,5
160	P/Q/L	12	10	13	12 - 98	max. 36	max. 36
160	P/Q/L	12	15	13	12 - 98	max. 41,5	max. 54
160	P/Q/L	12	20	13	12 - 98	max. 41,5	max. 62,5
190	P/Q/L	8	10	16	8 - 98	max. 41,5	max. 62,5
190	P/Q/L	8	15	16	8 - 98	max. 41,5	max. 62,5
190	P/Q/L	8	20	16	8 - 98	max. 41,5	max. 62,5

Type KS - Bracket type for wide cantilever brackets with matching bracket

Element width mm	Sheet type P	BSt Ø mm	Bracket spacing e in cm	Bracket spacing b in cm	Bracket height h in cm	Anchoring length for element length 83 cm l in cm	Anchoring length for panel length 125 cm l in cm
190	P/Q/L	10	10	16	10 - 98	max. 41,5	max. 56
190	P/Q/L	10	15	16	10 - 98	max. 41,5	max. 62,5
190	P/Q/L	10	20	16	10 - 98	max. 41,5	max. 62,5
190	P/Q/L	12	10	16	12 - 98	max. 41,5	max. 46
190	P/Q/L	12	15	16	12 - 98	max. 41,5	max. 62,5
190	P/Q/L	12	20	16	12 - 98	max. 41,5	max. 62,5
220	P/Q/L	8	10	19	8 - 98	max. 41,5	max. 62,5
220	P/Q/L	8	15	19	8 - 98	max. 41,5	max. 62,5
220	P/Q/L	8	20	19	8 - 98	max. 41,5	max. 62,5
220	P/Q/L	10	10	19	10 - 98	max. 41,5	max. 62,5
220	P/Q/L	10	15	19	10 - 98	max. 41,5	max. 62,5
220	P/Q/L	10	20	19	10 - 98	max. 41,5	max. 62,5
220	P/Q/L	12	10	19	12 - 98	max. 41,5	max. 57
220	P/Q/L	12	15	19	12 - 98	max. 41,5	max. 62,5
220	P/Q/L	12	20	19	12 - 98	max. 41,5	max. 62,5
240	P/Q/L	8	10	21	8 - 98	max. 41,5	max. 62,5
240	P/Q/L	8	15	21	8 - 98	max. 41,5	max. 62,5
240	P/Q/L	8	20	21	8 - 98	max. 41,5	max. 62,5
240	P/Q/L	10	10	21	10 - 98	max. 41,5	max. 62,5
240	P/Q/L	10	15	21	10 - 98	max. 41,5	max. 62,5
240	P/Q/L	10	20	21	10 - 98	max. 41,5	max. 62,5
240	P/Q/L	12	10	21	12 - 98	max. 41,5	max. 62,5
240	P/Q/L	12	15	21	12 - 98	max. 41,5	max. 62,5
240	P/Q/L	12	20	21	12 - 98	max. 41,5	max. 62,5