


## ISO-TRICK



ISO-TRICK for use on soft substrates, e.g. insulated ceilings and concrete floors.

The right concrete cover for every installation situation

Quick installation

Good connection with the concrete due to large openings in the strip

For horizontal reinforcement

Does not break or splinter when sawing on site

Extract from the information sheet for spacers:

According to DIN 4102, the currently common plastic spacers do not impair the fire resistance duration of the building components. Therefore, special requirements for the material of the spacers with regard to fire protection are not necessary.

Installation example:

For supporting rods of Ø 8-14 mm Consumption approx. 1.5 linear metres/m<sup>2</sup>.

Article description	Title of variant	Concrete cover mm	Packaging piece/ metre/ metre by the metre/ bucket/ bag/ bundle/ box/ can	Packaging metre/pallet	Weight kg/metre
50020240	ISO-TRICK 20	20	100 metres/bunch	6300 metres/pallet	0,150
50025280	ISO-TRICK 25	25	100 metres/bunch	4900 metres/pallet	0,175
50030210	ISO-TRICK 30	30	100 metres/bunch	4200 metres/pallet	0,265
50035230	ISO-TRICK 35	35	60 metres/bunch	3600 metres/pallet	0,295
50040270	ISO-TRICK 40	40	60 metres/bunch	2400 metres/pallet	0,322
50050250	ISO-TRICK 50	50	60 metres/bunch	1680 metres/pallet	0,600